

AD-A166 607

FUNDAMENTAL RELATIVISTIC SOLUTION FOR THE RAILGUN(U)
BATTELLE COLUMBUS LABS OH R L LIBOFF ET AL. APR 86
ARFSD-CR-86004 DARG29-81-D-0100


1/1

UNCLASSIFIED

F/G 20/3

NL





MICROCOPY

CHART

12

AD-A166 607

AD

AD-E401-487

CONTRACTOR REPORT ARFSD-CR-86004


**FUNDAMENTAL RELATIVISTIC SOLUTION
FOR THE RAILGUN**

**RICHARD L. LIBOFF
GREGORY K. SCHENTER
SCHOOL OF ELECTRICAL ENGINEERING
AND APPLIED PHYSICS
CORNELL UNIVERSITY
ITHACA, NY 14853**

**G. L. FERRENTINO
PROJECT ENGINEER
ARDC**

APRIL 1986

**DTIC
ELECTE
APR 14 1986
S D E**



**US ARMY
ARMAMENT
MUNITIONS &
CHEMICAL COMMAND
ARMAMENT R&D CENTER**

**U. S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER
FIRE SUPPORT ARMAMENT CENTER
DOVER, NEW JERSEY**

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

Destroy this report when no longer needed. Do not return to the originator.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Contractor Report ARFSD-CR-86004	2. GOVT ACCESSION NO. AD-A166607	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) FUNDAMENTAL RELATIVISTIC SOLUTION FOR THE RAILGUN		5. TYPE OF REPORT & PERIOD COVERED Interim Aug 85 to Dec 85
7. AUTHOR(s) Richard L. Liboff and Gregory K. Schenter, Cornell University G. L. Ferrentino, Project Engineer, ARDC		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS School of Electrical Engineering and Applied Physics Cornell University Ithaca, NY 14853		8. CONTRACT OR GRANT NUMBER(s) DAA G29-81-D-0100 (D.O. No. 1769, TCN 85-526)
11. CONTROLLING OFFICE NAME AND ADDRESS ARDC, IMD STINFO Div (SMCAR-MSI) Dover, NJ 07801-5001 (cont)		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) ARDC, FSAC Artillery Armament Div (SMCAR-FSA-E) Dover, NJ 07801-5001		12. REPORT DATE April 1986
		13. NUMBER OF PAGES 15
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution is unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES This research was supported in part by a contract with Battelle-Columbus Laboratory.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Railgun Electrons Relativistic Ohm's law Lorentz force Plasma		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A fully relativistic analysis is made of the dynamics of a railgun based on three assumptions: (1) Ohm's law is valid in the rest frame of the plasma, (2) total electron momentum is transferred to the projectile, and (3) motion of the projectile is constrained to one direction. With these assumptions, a rela- tivistic equation for the velocity of the projectile is obtained whose solution monotonically increases to one of two values depending on field strengths. For $B > E$, the maximum velocity is cE/B whereas for $E > B$ it is c where c is the speed of light, and E and B are applied electric and magnetic fields, respectively.		

DD FORM 1473
1 JAN 73

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

11. CONTROLLING OFFICE NAME AND ADDRESS: (cont)

Commander
U.S. Army Research Office
ATTN: AMXRO-PR
P.O. Box 12211
Research Triangle Park, NC 27709

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

CONTENTS

	Page
Introduction	1
Analysis	2
Application	6
Conclusions	6
References	9
Distribution List	11

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



INTRODUCTION

Attention has recently been given to dynamical properties of electromagnetic propulsion. In the rail-gun device,¹⁻⁵ a non-conducting projectile is propelled by a current-carrying plasma driven by the Lorentz force. Plasma dynamics is more difficult due to ablation of the projectile and for the most part previous studies have attempted to incorporate this effect.

In the present study, we return to a more elementary configuration for the purpose of developing a fully relativistic study of this problem. Thus, for example, it is assumed that the rest mass of the projectile is constant, and that total electron momentum from the plasma is transferred to the projectile. Furthermore, it is assumed that the projectile is constrained to move in one direction. Our remaining assumption is that Ohm's law is valid in the rest frame of the projectile.⁶

With these assumptions at hand, a relativistic equation is constructed for the projectile velocity. Solution to this equation reveals two asymptotic velocities which depends on initial field strengths. Thus, for example, for the case $E > B$, the velocity is c , the speed of light, whereas for $B > E$, the velocity is cE/B . It is further demonstrated that for initial velocities less than respective asymptotic values, velocities monotonically approach their respective limiting values. For the case $B > E$, starting velocities greater than cE/B are found to decay to this asymptotic value.

ANALYSIS

Our starting equation is Ohm's law, which in the rest frame of the projectile (primed coordinates) is written

$$\underline{J}' = \sigma \underline{E}' \quad (1)$$

where σ is conductivity. Transforming back to the lab frame (see Figure 1) we find

$$\begin{aligned} \gamma(J_x - c\beta\rho) &= \sigma E_x \\ J_y &= \sigma \gamma(E_y - \beta B_z) \\ J_z &= \sigma \gamma(E_z - \beta B_y) \end{aligned} \quad (2)$$

where $\beta \equiv v/c$ and $\gamma = (1 - \beta^2)^{-1/2}$. The charge density ρ , for a charge-neutral plasma, is equal to zero. In the lab frame we take

$$\underline{E} = E \hat{y} \quad (3)$$

$$\underline{B} = B \hat{z}$$

where hatted variables denote unit vectors. Inserting these values into (2) gives

$$\underline{J} = \sigma \gamma (E - \beta B) \hat{y} \quad (4)$$

with \underline{v} denoting microscopic electron velocity we write

$$\underline{J} = qn \langle \underline{v} \rangle \quad (5)$$

Electron charge and density are q and n respectively. We further recall that the density transforms as

$$n = \gamma n' \quad (6)$$

Combining the latter four equations gives

$$\langle \tilde{\mathbf{E}} \rangle = \mu (\mathbf{E} - \beta B) \hat{\mathbf{y}} \quad (7)$$

where

$$\mu \equiv \frac{\sigma}{qn'} \quad (8)$$

represents mobility in the rest frame.

Taking the average of the Lorentz force on electrons we obtain

$$\frac{d}{dt} \langle p_y \rangle = \frac{q}{c} \langle \tilde{\mathbf{E}}_y \rangle B \quad (9)$$

where we have recalled the vector property given by (7). We assume a total transfer of electron momentum to the projectile which gives

$$N \frac{d}{dt} \langle p_y \rangle \hat{\mathbf{y}} = \frac{d}{dt} \tilde{\mathbf{P}} \quad (10)$$

where N is total number of current-carrying electrons in the column. The momentum of the projectile, $\tilde{\mathbf{P}}$, is given by

$$\tilde{\mathbf{P}} = M \gamma \mathbf{v} \quad (11)$$

where M is the mass of the projectile.

Combining (7), (9), (10), and (11) gives the desired equation of motion

$$\frac{d}{dt} \gamma M v = \frac{qI}{c} \left(1 - \frac{v}{w}\right) B \quad (12)$$

where a is the length of the conducting column. I is the current

$$aI = NqeE \quad (13)$$

and

$$v = \frac{cE}{B} \quad (14)$$

Note in particular that from (13) we may write

$$E = \frac{I}{A\sigma} \quad (15)$$

where aA represents the volume of the conducting column in the rest frame.

Integrating (12) gives

$$\eta - \eta_0 = \frac{1}{c} \int_{v_0}^v \frac{du}{\left[1 - \left(\frac{u}{c}\right)^2\right]^{3/2} \left(1 - \frac{u}{w}\right)} \quad (15)$$

where η is the dimensionless time

$$\eta = \frac{aIBt}{Mc^2} \quad (16)$$

and $v = v_0$ at $\eta = \eta_0$. From (15) we see that $\eta \rightarrow \infty$ at the singular points $u = c$ and $u = w$ which represent asymptotic velocities. It will be shown below that these asymptotic velocities are approached monotonically. With this property we may conclude that for zero starting velocities maximum values are given by

$$E > B \quad v_{\max} = c \quad (17)$$

$$E < B \quad v_{\max} = w$$

A sketch of these findings is shown in Figure 2.

To examine the monotonicity of $v(t)$ we differentiate (12) to obtain

$$\frac{1}{c} \frac{dv}{d\eta} = \left[1 - \left(\frac{v}{c}\right)^2\right]^{3/2} \left[1 - \frac{v}{w}\right] \quad (18)$$

We conclude that for $v \leq c$ and $v \leq w$, $dv/d\eta \geq 0$. Furthermore, with $v = 0$ at $t = 0$, (18) gives the starting acceleration (in dimensional form)

$$\left. \frac{dv}{dt} \right|_0 = \frac{aIB}{Mc} \quad (19)$$

Note that for the case $E < B$, an initial velocity $v_0 > w$, decays to $v = w$ as is evident from (18). Furthermore, as is clear from (15), asymptotic values (17) are independent of initial velocities.

Characteristic times corresponding to the maximum velocities (17) are as follows. In the limit $w \gg c$, (12) gives the characteristic time

$$\tau_1 = \frac{Mc^2}{aIB} \quad (20)$$

with maximum velocity

$$v_{\max}^{(1)} = c \quad (20a)$$

In the limit $w \ll c$, (12) has the solution (with $v = 0$ at $t = 0$),

$$v = w [1 - \exp(-t/\tau_2)] \quad (21)$$

where

$$\tau_2 = \frac{E}{B} \tau_1 \quad (22)$$

and

$$v_{\max}^{(2)} = w \quad (22a)$$

We note that although $\tau_2 \ll \tau_1$, accelerations

$$\frac{v_{\max}^{(1)}}{\tau_1} = \frac{v_{\max}^{(2)}}{\tau_2}$$

are the same.

APPLICATION

In applying the preceding results to experimental values, first we rewrite w in practical units. Setting

$$E = \frac{V}{a} \quad (19)$$

where V is the potential across the rails, permits (14) to be rewritten

$$w = \frac{cV}{aB} \quad (20)$$

In practical units this expression becomes

$$w \left(\frac{\text{km}}{\text{s}} \right) = \frac{10^3 V(\text{kV})}{B(\text{kgauss})a(\text{cm})} \quad (21)$$

Typical experimental values are^{5,7}: $V = 1\text{kV}$, $a \approx 1\text{cm}$, $B \approx 200\text{ kgauss}$ which gives $w \approx 5\text{km/s}$. This value agrees in order-of-magnitude with observed maximum velocities.

CONCLUSIONS

We have examined the relativistic solution to the rail-gun configuration. Incorporating some simplifying assumptions we found that the projectile velocity goes monotonically to the minimum of the two velocities, c and cE/B . The asymptotic value c corresponds to $E < B$ whereas the value cE/B corresponds to the limit $B > E$. It should be emphasized that this present study does not take into account thermodynamic effects such as momentum imparted to the projectile from the exploding "fuse."




Figure 1. Lab frame and rest frame




Figure 2. Sketches of dimensionless time, η , as a function of projectile velocity v ,
 with $v = 0$ at $t = 0$

REFERENCES

1. I. R. McNab, Journal of Applied Physics, vol 51, 1980, p 2549.
2. J. D. Powell and J. H. Batteh, Journal of Applied Physics, vol 52, 1981, p 2717.
3. J. D. Powell and J. H. Batteh, Journal of Applied Physics, vol 54, 1983, p 2242.
4. J. H. Batteh, Journal of Applied Physics, vol 56, 1984, p 3182.
5. Collection of papers on electromagnetic propulsion, IEEE Trans. on Magnetics, mag 20, March 1984.
6. J. D. Jackson, Classical Electrodynamics, 2nd ed., John Wiley, New York, 1975.
7. G. Ferrentino, personal communication.

DISTRIBUTION LIST

Commander
Armament Research and Development Center
U.S. Army Armament, Munitions
and Chemical Command
ATTN: SMCAR-FSA-E (5)
SMCAR-MSI (5)
SMCAR-SF
Dover, NJ 07801-5001

Commander
U.S. Army Armament, Munitions
and Chemical Command
ATTN: AMSMC-QAR-R(D)
Dover, NJ 07801-5001

Administrator
Defense Technical Information Center
ATTN: Accessions Division (12)
Cameron Station
Alexandria, VA 22304-6145

Director
U.S. Army Materiel Systems
Analysis Activity
ATTN: AMXSY-MP
Aberdeen Proving Ground, MD 21005-5066

Commander
Chemical Research and Development Center
U.S. Army Armament, Munitions
and Chemical Command
ATTN: SMCCR-SPS-IL
Aberdeen Proving Ground, MD 21010-5423

Commander
Chemical Research and Development Center
U.S. Army Armament, Munitions
and Chemical Command
ATTN: SMCCR-RSP-A
Aberdeen Proving Ground, MD 21010-5423

Director
Ballistic Research Laboratory
ATTN: AMXBR-OD-ST
Aberdeen Proving Ground, MD 21005-5066

Chief
Benet Weapons Laboratory, CCAC
Armament Research and Development Center
U.S. Army Armament, Munitions
and Chemical Command
ATTN: SMCAR-CCB-TL (2)
Watervliet, NY 12189-5000

Commander
U.S. Army Armament, Munitions
and Chemical Command
ATTN: SMCAR-ESP-L
Rock Island, IL 61299-6000

Director
U.S. Army TRADOC Systems
Analysis Activity
ATTN: ATAA-SL
White Sands Missile Range, NM 88002

Director
Defense Advanced Research
Projects Agency
ATTN: DARPA-TTO, H. D. Fair, Jr. (5)
1400 Wilson Boulevard
Arlington, VA 22209

Commander
U.S. Army Strategic Defense Command
ATTN: DASD-DP, LTC N. Cooney (2)
P.O. Box 15280
Arlington, VA 22215-0151

System Planning Corporation
ATTN: Donald E. Shaw
1500 Wilson Boulevard
Arlington, VA 22209-2454

Center for Electromechanics
ATTN: W. Weldon (2)
10100 Burnet Road
Austin, TX 78758

Commander
HQ, AFSC/DLWA
ATTN: CPT R. Reynolds
Andrews Air Force Base, MD 20334

Commander
Naval Sea Systems Command
ATTN: LCDR Joseph R. Costa
Washington, DC 20362

Commander
Air Force Armament Technology Laboratory
ATTN: DLDG, Timothy Aden
Eglin Air Force Base, FL 32542-5270

Commander
U.S. Army Research Office
ATTN: AMXRO-PR, H. T. Throckmorton
P.O. Box 12211
Research Triangle Park, NC 27709

Commander
Strategic Defense Initiative Organization
ATTN: SDIO/KEW, BG M. O'Neil (2)
Washington, DC 20301-7100

Electromagnetic Launch Research, Inc.
ATTN: Henry Kolm
Peter P. Mongeau
625 Putnam Avenue
Cambridge, MA 92139

Westinghouse Electric Company
ATTN: Lan R. McNab, Manager,
EML Engineering
Marine Division, MS ED-5
401 E. Hendy Avenue
P.O. Box 499
Sunnyvale, CA 94088

Brookhaven National Laboratory
ATTN: James R. Powell, Jr., Head,
Fusion Technology Group
Building 820M
Upton, NY 11973

General Electrical Company
ATTN: Alan Wait, Manager,
EML Systems Technology
RD-3 Plains Road
Ballston Spa, NY 12020

END
FILMED

5-86

DTIC